

MCS 401 – Computer Algorithms I  
Spring 2017  
Problem Set 6

Lev Reyzin

**Due:** 4/28/17 by the beginning of class

**Instructions:** Atop your problem set, write your name and whether you are an undergraduate or graduate student. Also write the names of all the students with whom you have collaborated on this problem set.

**1. [10 pts]** We define the decision version of the Minimum Cut problem as follows: given an undirected, unweighted graph  $G = (V, E)$  two distinct vertices  $s, t \in V$ , and a number  $k$ , does there exist an  $s-t$  cut of value at most  $k$ ?

For each of the two questions below, decide whether the answer is (i) “Yes”, (ii) “No”, or (iii) “Unknown, because it would resolve the question of whether  $\mathcal{P} = \mathcal{NP}$ .” Give an explanation of your answers.

(a) Question: Is it the case that Minimum Cut  $\leq_p$  Vertex Cover?

(b) Question: Is it the case that Independent Set  $\leq_p$  Minimum Cut?

**2. [10 pts]** Consider a set of clauses  $C_1, \dots, C_k$  over  $x_1, \dots, x_n$  consisting of *unnegated* variables, for example  $(x_1 \vee x_3 \vee x_4 \vee x_7)$ . Satisfying a collection of clauses over unnegated variables is easy – simply set all the variables appearing in the clauses to 1. However, it is natural to ask whether it is possible to set no more than  $k$  variables to 1 and still satisfy such a collection of clauses. Prove that this is NP-complete.

**3. [10 pts]** Suppose someone gives you a black-box  $B$  that takes in any undirected graph  $G = (V, E)$  and a number  $k$ , and in unit time it returns “yes” if  $G$  has an independent set of size at least  $k$  and “no” otherwise. Design an algorithm with the power to access  $B$  as many times as it wishes that returns an independent set of maximum cardinality in a given graph in polynomial time.

**4. [10 pts]** Given objects  $p_1, \dots, p_n$ , and distances  $d(\cdot, \cdot)$  on them (with  $d(p_i, p_i) = 0$ ,  $d(p_i, p_j) = d(p_j, p_i)$ , and  $d(p_i, p_j) > 0$  for  $i \neq j$ ), consider the clustering problem of dividing the objects into  $k$  sets so as to maximize the minimum distance between any pair of objects in distinct clusters. Give a polynomial time algorithm to solve this (*hint: use minimum spanning trees*).

A different but seemingly related way to formalize the clustering problem would be as follows: divide the objects into  $k$  sets so as to minimize the maximum distance between any pair of objects

in the same cluster. Whereas the formulation in the previous paragraph sought clusters so that no two were “close,” this new formulation seeks clusters so that none of them is too “wide.”

Given the similarities, it is perhaps surprising that this new formulation is computationally hard to solve optimally. First, let's write it first as a yes/no decision problem: given  $n$  objects  $p_1, \dots, p_n$ , with distances on them as before, a number  $k$ , and a bound  $B$ , we can ask: can the objects be partitioned into  $k$  sets, so that no two points in the same set are at distance greater than  $B$  from one another?

Prove that this new formulation is NP-complete.